


**130504  
CT SERIES  
DESICCANT  
CARTRIDGE  
REPLACEMENT**

PATENT NO. 7361214




**NOTE**

DO NOT OPEN DESICCANT CARTRIDGE.  
FOR MSDS GO TO [www.autorefinishdevilbiss.com](http://www.autorefinishdevilbiss.com)


**⚠ WARNING**

TANK UNDER PRESSURE.  
SHUT OFF AIR SUPPLY AND RELEASE PRESSURE BEFORE SERVICING.

1. Shut off air and open drain valve located at the bottom of the CT30 to relieve pressure.
2. Remove 6 screws in lid using a 14 mm socket wrench. Remove lid. Avoid damaging gasket.
3. Remove the used desiccant cartridge and inspect tank outlet. If black plastic bushing is present, remove and insert new, high-efficiency orange bushing into tank outlet.



4. Insert new desiccant cartridge.
5. Reinstall lid and screws. Tighten screws to a minimum 25-30 ft. lbs. Tighten in order shown at right:
6. Turn on air supply.
7. Moisture indicator should turn back to green within 12 hours.



**DeVilbiss Worldwide Sales and Service Listing:**  
[www.autorefinishdevilbiss.com](http://www.autorefinishdevilbiss.com)


**DeVilbiss Automotive Refinishing**

DeVilbiss has authorized distributors throughout the world. For equipment, parts and service, check the Yellow Pages under "Automotive Body Shop Equipment and Supplies." For technical assistance, see listing below.

**U.S.A./Canada Customer Service Office:**  
11360 S. Airfield Road, Swanton, OH 43558  
Toll-Free Telephone: 1-800-445-3988 (U.S.A. and Canada only)

**130504  
CT SERIES  
DESICCANT  
CARTRIDGE  
REPLACEMENT**

PATENT NO. 7361214




**NOTE**

DO NOT OPEN DESICCANT CARTRIDGE.  
FOR MSDS GO TO [www.autorefinishdevilbiss.com](http://www.autorefinishdevilbiss.com)


**⚠ WARNING**

TANK UNDER PRESSURE.  
SHUT OFF AIR SUPPLY AND RELEASE PRESSURE BEFORE SERVICING.

1. Shut off air and open drain valve located at the bottom of the CT30 to relieve pressure.
2. Remove 6 screws in lid using a 14 mm socket wrench. Remove lid. Avoid damaging gasket.
3. Remove the used desiccant cartridge and inspect tank outlet. If black plastic bushing is present, remove and insert new, high-efficiency orange bushing into tank outlet.



4. Insert new desiccant cartridge.
5. Reinstall lid and screws. Tighten screws to a minimum 25-30 ft. lbs. Tighten in order shown at right:
6. Turn on air supply.
7. Moisture indicator should turn back to green within 12 hours.



**DeVilbiss Worldwide Sales and Service Listing:**  
[www.autorefinishdevilbiss.com](http://www.autorefinishdevilbiss.com)

**DeVilbiss Automotive Refinishing**

DeVilbiss has authorized distributors throughout the world. For equipment, parts and service, check the Yellow Pages under "Automotive Body Shop Equipment and Supplies." For technical assistance, see listing below.

**U.S.A./Canada Customer Service Office:**  
11360 S. Airfield Road, Swanton, OH 43558  
Toll-Free Telephone: 1-800-445-3988 (U.S.A. and Canada only)